

specifications

DYN-1220

Order No: 416819

Vacuum Motor:

3 HP By-Pass; Continuous Duty

Voltage: 460 (3-Phase, 60 Hz)

Waterlift: 78"

CFM: 180

Sound Level: 68dB

Inlet: 2"

Capacity: 9 Gal Collector Pan

Filter: 13 Sq Ft MicroClean

DYN-2220

Order No: 457620

Vacuum Motor:

(2) 2.3 HP, By-Pass;

Intermittent

Voltage: 115

Waterlift: 97"

CFM: 200

Inlet: 2"

Capacity: 9 Gal Collector Pan

Filter: 13 Sq Ft MicroClean

DYN-2320

Order No: 458651

Vacuum Motor:

(3) 4 HP By-Pass; Intermittent

Voltage: 115

Waterlift: 75"

CFM: 280

Inlet: 3"

Capacity: 9 Gal Collector Pan

Filter: 13 Sq Ft MicroClean



DYN-1220



DYN-2220



DYN-2320

The Dynavac®'s are designed for the removal of fine abrasive dust such as concrete without a premature filter clogging while returning clean air back into the workplace.

The fiberglass housing is non-corrosive, dent and rustproof, perfect for any rugged environment. The low inlet and counterbalanced base ensures the vacuum will never tip over. The external filter shaker keeps the filter clean resulting in minimal filter maintenance.

The state of the art filter system is rated at 99.9% efficient @ .5 microns. There are no bags or pre-filters required, saving you money. The collector pan slides out easy from under the vacuum for quick disposal of debris.

The continuous duty vacuum is virtually maintenance-free, our unique multi-stage turbines offer more suction using less horse power than that of any other vacuum blower on the market.

