

## Pump-Out Vacuum / Adaptor

### specifications

#### **P42010SMP** Wet (431001)

*Vacuum Motor:*  
120 Volt, 2 Stage 1.3 HP  
By-Pass;  
94 CFM - Waterlift 84"  
*Current:* 7.5 AMPS  
*Sound Level:* 78dB  
*Pump:* 60 Hz, 120V  
*Pump Waterlift:* 44 GPM @ 40 Ft.  
*Pump Current:* 8.0 AMPS  
*Tank Capacity:* 20 Gallon Poly  
*Power Cord:*  
50 Ft, 12/3 Wire Grounded  
w/Ground Fault Interrupter,  
Safety Yellow

#### **SMP-1 Adaptor** (307319)

*Pump:* 120V, 60 Hz  
*Pump Waterlift:* 28 GPM @ 23 Ft  
*Pump Current:* 8.0 AMPS



The pump-out vacuum and adaptor are especially effective when vacuuming up liquid spills, leaks, for flood control and swimming pool maintenance.



The SMP-1 adaptor is designed to fit the P415 and P420 poly or #15 and #20 steel wet/dry vacuums or drum adaptors.

It is easy to install, no special tools or equipment are required. All you need is a tank vacuum or drum adaptor, set up for wet pickup and a 3/4" garden hose or 1 1/2" hose.

The SMP-1 adaptor includes a conversion adaptor w/swivel hose connector, 4 Ft vinyl hose, barbed hose connector, support cord w/handle, mesh filter bag and power cord w/ground fault interrupter.

Liquids are recovered in the tank and continuously pumped out, this is especially useful in emergency situations.

P42010SMP features a 1.3 HP motor head, 20 gallon poly tank w/built-in pump and includes a barbed connector, It is shipped with a 15 Ft intake hose, 50 Ft discharge hose, mesh filter bag, 5 Ft metal wand, 16" squeegee and 12" gulper tool.

### specifications

*Vacuum Motor:*  
120 Volt, 2 Stage 2 HP By-Pass;  
112 CFM - Waterlift 106"  
*Current:* 11.0 AMPS  
*Sound Level:* 75dB  
*Power Cord:*  
30 Ft, 18/3 Wire Grounded  
Safety Yellow  
*Tools Includes:*  
10 Ft Hose w/Hose Connector;  
Hose Cage; 5 Ft, 2 Pc Metal Wand;  
14" Metal Floor Tool

#### **DYN-812D** Dry (459852)

*Recovery Capacity:* 8 Gal Dry

#### **DYN-1012D** Dry (459895)

*Recovery Capacity:* 10 Gal Dry



## Dynavac® Dry Concrete

These compact vacuums are designed to be used with the multi-purpose floor machine for clean up of concrete and wood dust, reducing the incidence of airborne dust.

The durable steel motor head is equipped with powerful 2 HP motor head.

Cold rolled steel tanks have a hammermark finish and features reinforcing ribs to strengthen tanks for handling higher waterlift.

It is equipped with a concrete shaker filter system specially designed to keep the cloth filter from clogging.



The filtration system includes a deep wire frame and concrete cloth filter.

The tank has four 2 1/2" swivel casters and three heavy-duty chrome plated spring steel holddown clamps to ensure a positive vacuum seal.