

specifications

Vacuum Motor:
120 Volt, 2 Stage 1.3 HP By-Pass;
94 CFM - Waterlift 84"
Current: 7.5 AMPS
Sound Level: 78dB
Recovery Capacity: .70 Bu Dry
Power Cord:
30 Ft, 18/3 Wire Grounded

P4710HVAF (369888)
with 1 1/4" Dry Tool Kit
Tool Kit Includes:
10 Ft Hose; Hose Connector;
(2) Straight Wands; Crevice Tool;
2-Way Carpet Tool; Floor Tool
Upholstery Tool; Dusting Brush

P4710DAF (369861)
with 1 1/2" Dry Tool Kit
Tool Kit Includes:
10 Ft Hose w/Hose Connector;
Metal Wand; Crevice Tool; Floor;
Tool; Upholstery Tool; Carpet Tool



P4710DAF

specifications

410SSDAF (302775)
with 1 1/2" Tool Kit
Vacuum Motor:
120 Volt, 2 Stage 1.3 HP By-Pass;
94 CFM - Waterlift 84"
Current: 7.5 AMPS
Sound Level: 78dB
Recovery Capacity: .40 Bu Dry
Power Cord:
30 Ft, 18/3 Wire Grounded
Safety Yellow

MAV-410SSDAF (325724)
with 1 1/2" Tool Kit
Venturi Head: Non Electric
CFM*: 170 Output / Working 100
Recovery Capacity: .40 Bu Dry
*Based on ID 1/2" airline @ 70 CFM,
90 PSI Minimum Requirement

Dry Tool Kit Includes:
10 Ft Hose w/Hose Connector;
Metal Wand; Crevice Tool; Floor
Tool; Upholstery Tool; Carpet Tool



410-SSDAF



MAV-410SSDAF

EnviroMaster™ 7 Dry HEPA

Easy to carry and transport, this compact vacuum is suited for cleanup in small and confined areas.

The filter system consists of a certified absolute 12" HEPA filter, intermediary 2 ply micro filter and 2 ply disposable filter bag.

The HEPA filter has a minimum efficiency rating of 99.97% at 0.3 microns HOT DOP method certified @ 100 CFM.

The tank is rotationally molded, of high impact plastic with 1/4" wall constructions. No-tip base design has low center of gravity.

Equipped with four 2 1/2" swivel casters and three heavy-duty chrome plated spring steel holddown clamps to ensure a positive vacuum seal.



Vacuums are shipped with HEPA filter, intermediary 2 ply disposable filter bag (5/Pk), and dry tool kit.

HEPA Dry Backpack

This lightweight stainless steel backpack vacuum is excellent for use in hard to reach areas and are available in electric and air-operated models.

The filter system consists of a certified absolute 12" HEPA filter intermediary 2 ply micro filter and 2 ply disposable filter bag.

The HEPA filter has a minimum efficiency rating of 99.97% at 0.3 microns HOT DOP method certified @ 100 CFM.

The vacuum tank is fabricated of high quality, heavy-duty stainless steel that protects against corrosion.

Strap it on your back, the 410SS is especially useful to clean in hard to reach and limited access areas.

The easily detachable back frame can be removed to create a lightweight canister vacuum.

The electric unit is equipped with a durable poly head with 1.3 HP by-pass motor

The air-operated vacuum has a durable steel venturi head and is designed with a built-in safety pressure control and gauge.

The automatic pressure release safety valve on the MAV-410 is pre-set at the factory to maintain constant operation efficiency.



The vacuums are shipped with HEPA filter, intermediary 2 ply disposable filter bag (5/Pk), 2 ply micro filter (2/Pk), and dry tool kit.