

## Pump-Out Vacuum / Adaptor

### specifications

#### **P42010SMP** Wet (431001)

*Vacuum Motor:*  
120 Volt, 2 Stage 1.3 HP  
By-Pass;  
94 CFM - Waterlift 84"  
*Current:* 7.5 AMPS  
*Sound Level:* 78dB  
*Pump:* 60 Hz, 120V  
*Pump Waterlift:* 44 GPM @ 40 Ft.  
*Pump Current:* 8.0 AMPS  
*Tank Capacity:* 20 Gallon Poly  
*Power Cord:*  
50 Ft, 12/3 Wire Grounded  
w/Ground Fault Interrupter,  
Safety Yellow

#### **SMP-1 Adaptor** (307319)

*Pump:* 120V, 60 Hz  
*Pump Waterlift:* 28 GPM @ 23 Ft  
*Pump Current:* 8.0 AMPS



The pump-out vacuum and adaptor are especially effective when vacuuming up liquid spills, leaks, for flood control and swimming pool maintenance.

Liquids are recovered in the tank and continuously pumped out, this is especially useful in emergency situations.

P42010SMP features a 1.3 HP motor head, 20 gallon poly tank w/built-in pump and includes a barbed connector, It is shipped with a 15 Ft intake hose, 50 Ft discharge hose, mesh filter bag, 5 Ft metal wand, 16" squeegee and 12" gulper tool.



The SMP-1 adaptor is designed to fit the P415 and P420 poly or #15 and #20 steel wet/dry vacuums or drum adaptors.

It is easy to install, no special tools or equipment are required. All you need is a tank vacuum or drum adaptor, set up for wet pickup and a 3/4" garden hose or 1 1/2" hose.

The SMP-1 adaptor includes a conversion adaptor w/swivel hose connector, 4 Ft vinyl hose, barbed hose connector, support cord w/handle, mesh filter bag and power cord w/ground fault interrupter.

### specifications

*Vacuum Motor:*  
120 Volt, 2 Stage 2 HP By-Pass;  
112 CFM - Waterlift 106"  
*Current:* 11.0 AMPS  
*Sound Level:* 75dB  
*Power Cord:*  
30 Ft, 18/3 Wire Grounded  
Safety Yellow  
*Tools Includes:*  
10 Ft Hose w/Hose Connector;  
Hose Cage; 5 Ft, 2 Pc Metal Wand;  
14" Metal Floor Tool

#### **DYN-812D** Dry (459852)

*Recovery Capacity:* 8 Gal Dry

#### **DYN-1012D** Dry (459895)

*Recovery Capacity:* 10 Gal Dry



## Dynavac® Dry Concrete

These compact vacuums are designed to be used with the multi-purpose floor machine for clean up of concrete and wood dust, reducing the incidence of airborne dust.

The durable steel motor head is equipped with powerful 2 HP motor head.

Cold rolled steel tanks have a hammermark finish and features reinforcing ribs to strengthen tanks for handling higher waterlift.

It is equipped with a concrete shaker filter system specially designed to keep the cloth filter from clogging.



The filtration system includes a deep wire frame and concrete cloth filter.

The tank has four 2 1/2" swivel casters and three heavy-duty chrome plated spring steel holddown clamps to ensure a positive vacuum seal.