

specifications

Vacuum Motor:
5/8 HP, 120 Volt - 200 CFM
Brush Speed:
SV Models - 3500 RPM
SVG Models - 1650 RPM
Brush Size: 3" Diameter
Inlet: 3 1/2" Diameter
Capacity: 1.2 Bushel
Power Cord:
60 Ft., 16 Gauge/3 Wire Grounded
Rear Wheels: Two 6" Transport
Front Casters:
Two 2" Double Wheel Swivel

SV-240 (380318)

SVG-241 (317608)

Current: 8.0 AMPS
Cleaning Path: 24" Wide
Dimensions:
34 1/2" L X 25 1/4" W X 36 1/2" H

SV-280 (380326)

SVG-281 (317624)

Current: 8.5 AMPS
Cleaning Path: 28" Wide
Dimensions:
34 1/2" L X 29" W X 36 1/2" H



SV240 / SVG-241



SV280 / SVG-281



XA-300C

specifications

XA-300C (444960)

Motor:
120 Volt, 1/2 HP - 3 Speed
1500 - 2000 - 2500 CFM
Switch: 3 Speed Rotary
Power Cord:
25 Ft., 16/3 Wire Grounded

SV / SVG Wide Area

Clean large open areas more efficiently with SV and SVG wide area vacuums.

Easy to operate and maneuver, embedded dirt and debris are picked up and removed, leaving carpets clean and groomed.

The L-shape/low profile is designed to clean around and under furniture with wrap around bumper to protect furniture and walls from damage.

Chevron pattern brush with four rows of bristles is designed for grooming. Dirt and debris is moved towards the center, while the "no-fling" brush barrier contains and directs the dirt and debris into an oversized vacuum inlet for maximum pickup.

Top-fill system assures maximum performance and pickup, while the 3.5" inlet eliminates clogging at the intake.

The unit's pile height adjusts to five settings allowing for maximum cleaning efficiency.

Heavy-duty construction with a welded steel chassis that is mounted on a structural foam housing, provides added durability and strength; yet they are lightweight (under 75 lbs.) with excellent maneuverability.

Equipped with a heavy-duty dust retentive cloth outer filter bag and large 1.2 bushel capacity disposable paper filter bag.



The chrome plated steel handle folds for convenient storage and transport.

SVG Vac-N-Groom™ models are equipped with a cog and three track V-belt drive system with a 2-to-1 ratio that increases torque and power assists forward movement while enhancing the unit CFM.

XA-300C Floor Dryer

Use the airmover for the quick drying of carpeted or hard floors and room ventilation.

Rotationally molded of hi-density polyethylene, won't dent and is corrosion resistant.

The cord wrap is molded into housing for convenient storage of the power cord.

The XA-300C can be used in four positions, normal, flat on its back, stacked or tilted at 45 degrees.