

specifications

MD-10A (10" - 340200)

MD-13A (13" - 355062)

Motor:

1/3 HP, 120V-60 Cycle, 56 Frame

Current: 6.4 AMPS

Gears: 2 Idler

Brush Speed: 175 RPM

Transport Wheels: 3"

MD-13B (13" - 358916)

MD-15B (15" - 355011)

Motor:

1/2 HP, 120V-60 Cycle, 66 Frame

Current: 8 AMPS

Gears: 2 Idler

Brush Speed: 175 RPM

Transport Wheels:

3" - MD-13B; 5" - MD-15B

MD-15D (15" - 355046)

MD-17D (17" - 351954)

MD-20D (20" - 351962)

MD-21D (21" - 360422)

Motor:

1 HP, 120V-60 Cycle, 66 Frame

Current: 13.2 AMPS

Gears: 3 Idler

Brush Speed: 175 RPM

Transport Wheels: 5"

MD-20E (20" - 357073)

MD-21E (21" - 364126)

MD-24E (24" - 351938)

Motor:

1 1/2 HP, 120V-60 Cycle,

66 Frame; Dual Capacitor

Current: 15 AMPS

Gears: 3 Idler

RPM: 175

Transport Wheels:

MD20E & MD21E- 5"; MD24E- 4"

MH-17E (17" - 358010)

MH-20E (20" - 358029)

Motor:

1 1/2 HP, 120V-60 Cycle,

66 Frame; Dual Capacitor

Current: 15 AMPS

Gears: 3 Idler

Brush Speed: 250 RPM

Transport Wheels: 5"

175 RPM / 250 RPM Floor Machines

Our standard and high speed floor machines are available in a variety of brush sizes and motor horsepower to meet the various needs of floor care professionals. They are field-tested to withstand the demanding heavy duty use required for stripping, scrubbing and polishing hard surface flooring.

MD-15

MD-20

MD-24

MD-17 Shown w/Optional Solution Tank

MD-10

MD-13

Overdose Handle Grips
For operator's comfort.

Flexible Dual Triggers
Left or right hand operation, non-conductive with built-in safety lock-out to prevent accidental startup.

Heavy-Duty Switch
Is set in a die cast aluminum switch box, which won't chip or rust.

50 Ft Power Cord
3-Wire grounded with water resistant jacket.

4 Gallon Solution Tank (Optional)
Dispenses liquid for scrubbing and polishing. (334898).

All Steel Gear System*
Triple planetary, permanently lubricated with specially designed flex coupler to guard against possible motor damage when under load.

Steel Clamp Lever
Adjusts handle position.

Aluminum Apron
For added strength and rigidity, also shields the transport wheels to prevent damage.

Non-Marring Bumpers
Prevents damage to furniture and walls.

Wheel Support System
Extra heavy reinforced six point cast aluminum.

* Except 1/3 HP and 1/2 HP floor