

## Wet / Dry Tank Vacuums

### Push Handle

Chrome plated steel on glidemobile units.

### Motor Head Assemblies

Durable steel or cast aluminum with choice of 1, 1.3, 2, or 2.3 HP motors. Equipped with 30 Ft. 3 wire grounded safety yellow line cord.

### Holddown Clamps

Chrome plated spring steel with non-marring tips to ensure a positive vacuum seal.

### Rotationally Molded Tank

High impact plastic, won't leak or dent and resist chemical attack.

### 8" Rear Wheels

On glidemobile style vacuums.

### Ball Bearing Swivel Casters

5, 8 and 16 gallon tanks are equipped with 2 1/2" casters and 20 gallon tanks with 3" casters.

"Trap-Sack"® dry filtration system is standard on all vacuums. Includes removable cloth filter and large totally enclosed disposable paper filter bag for greater filtration area. The filter bag makes it easy to dispose of the collected material.

Wet pickup adaptor is included with all wet/dry vacuums. The automatic float shutoff protects the by-pass motor from water damage.

The 1 1/2" swivel hose connector fits tank inlet for vacuuming or motor head exhaust fitting (on most models) for blowing applications. Optional 1 1/4" and 2" connectors are available.

Convenience outlet is built-in to most motor heads for use with an electric power nozzle.



P41535W



The dry and wet/dry vacuum are equipped with the following tools:

- 5 Ft Metal Wand
- 10 Ft Vinyl Hose
- 1 1/2" Swivel Hose Connector
- 14" Metal Carpet Tool
- 14" Metal Floor Tool
- 11" Plastic Crevice Tool
- 6" Upholstery Tool
- 14" Metal Squeegee (Wet/Dry Kit Only)

The 16 and 20 gallon poly tanks are equipped with a gate valve.



P4810W



P4512W



P42035W

**Note:** See the Mastercraft Professional Equipment Line Price List for our full line of dry and wet/dry tank vacuums.

## specifications

**1.3 HP Wet/Dry Vacuums**  
with 1 1/2" Wet/Dry Tool Kit  
*Vacuum Motor:*  
120 Volt, 2 Stage By-Pass;  
94 CFM - Waterlift 84"

**P4510W** (369853)  
*Recovery Capacity:*  
5 Gallon Wet / .70 Bu Dry

**P4810W** (371777)  
*Recovery Capacity:*  
8 Gallon Wet / 1.10 Bu Dry

**2 HP Wet/Dry Vacuums**  
with 1 1/2" Wet/Dry Tool Kit  
*Vacuum Motor:*  
120 Volt, 2 Stage By Pass  
112 CFM - Waterlift 106"

**P4812W** (319562)  
*Recovery Capacity:*  
8 Gallon Wet / 1.10 Bu Dry

**P41512W** (319600)  
*Recovery Capacity:*  
16 Gallon Wet / 2.00 Bu Dry

**P42012W** (328707)  
*Recovery Capacity:*  
20 Gallon Wet / 2.20 Bu Dry

**2.3 HP Wet/Dry Vacuums**  
with 1 1/2" Wet/Dry Tool Kit  
*Vacuum Motor:*  
120 Volt, 2 Stage By Pass;  
115 CFM - Waterlift 110"

**P4815W** (371785)  
*Recovery Capacity:*  
8 Gallon Wet / 1.10 Bu Dry

**P41515W** (375128)  
*Recovery Capacity:*  
16 Gallon Wet / 2.00 Bu Dry

**P42015W** (328898)  
*Recovery Capacity:*  
20 Gallon Wet / 2.20 Bu Dry

**2 HP Wet/Dry Vacuums**  
with 1 1/2" Wet/Dry Tool Kit  
*Vacuum Motor:*  
120 Volt, 3 Stage By Pass;  
92 CFM - Waterlift 135"

**P4835W** (411728)  
*Recovery Capacity:*  
8 Gallon Wet / 1.10 Bu Dry

**P41535W** (329800)  
*Recovery Capacity:*  
16 Gallon Wet / 2.00 Bu Dry

**P42035W** (318701)  
*Recovery Capacity:*  
20 Gallon Wet / 2.20 Bu Dry

Note: See page 22 for complete vacuum specifications.